

INDIRECT F-D PV PAR-V2 FDH G5 4X24W, ECG, 9003

ORDER CODE: IBKA10221483000

Mounting	Ceiling recessed
Lamps	Linear fluorescent lamp FDH
Optical system	Parabolic louvre (PAR-V2)
Light distribution	Direct
Wiring	Electronic control gear On request: Dimmable electronic control gear (1-10V/ switch DIM/DSI/DALI)
Materials	Housing: sheet steel Parabolic louvre: polished aluminium sheet
Surface finish	Powder coat finish – white (RAL 9003); other colors on request
Accessories	Mounting brackets On request: Safety wire Connectors: 3-pole Wieland gesis GST 18i3, Wago Winsta 770, ISODOM, 5-pole connectors Wieland gesis GST 18i5, Wago Winsta 770, ISODOM




Standard





On Request



Lighting Curve




Picture



Type	optics	power	lamp	picture	dimensions				emergencyweight				
	PAR-V2	(W)			A1	A2	L1	L2	H1	H2	1H	3H	(kg)
INDIRECT F-D PV	●	2x14	FDH	1,3	595	573	595	585	100	7	●	●	5,7
INDIRECT F-D PV	●	2x24	FDH	1,3	595	573	595	585	100	7	●	●	5,7

Type	optics PAR-V2	power (W)	lamp	picture	dimensions				emergency				weight
					A1	A2	L1	L2	H1	H2	1H	3H	(kg)
INDIRECT F-D PV	•	4x14	FDH	2,3	595	573	595	585	100	7	•	•	5,7
INDIRECT F-D PV	•	4x24	FDH	2,3	595	573	595	585	100	7	•	•	5,7

Mounting Type



The Company reserves the right to change any product specifications without prior notification.

Last Updated:01.03.2012